

## PXC Modular Series



Figure 1. PXC Modular.

### Description

The PXC Modular (Programmable Controller - Modular) is an integral part of the APOGEE<sup>®</sup> Automation System. It is a high performance, modular Direct Digital Control (DDC) supervisory field panel.

The field panel operates stand-alone or networked to perform complex control, monitoring, and energy management functions without relying on a higher level processor.

- Up to 100 modular field panels communicate on a peer-to-peer network.
- With the addition of TX-I/O modules and a TX-I/O Power Supply on a self-forming bus, the PXC Modular can directly control up to 500 points.

With the addition of an Expansion Module, the PXC Modular also provides central monitoring and control for distributed Field Level Network (FLN) devices.

### Features

- Modular hardware components match initial control requirements while providing for future expansion.
- DIN rail mounting and removable terminal blocks simplify installation and servicing.
- Proven program sequences to match equipment control applications.
- Sophisticated Adaptive Control, a closed loop control algorithm that auto-adjusts to compensate for load/seasonal changes.
- Built-in energy management applications and DDC programs for complete facility management.
- Comprehensive alarm management, historical data trend collection, operator control and monitoring functions.
- Support for peer-to-peer communications over Industry standard 10/100Base-T TCP/IP networks.

## Hardware

### PXC Modular

- The PXC Modular is a microprocessor-based multi-tasking platform for program execution and communication with other field panels. It scans field data, optimizes control parameters, and manages operator requests for data in seconds.
- The program and database information stored in the PXC Modular memory is battery-backed. This eliminates the need for time-consuming program and database re-entry in the event of an extended power failure. When battery replacement is necessary, the PXC Modular illuminates a “battery low” status LED and can send an alarm message to selected printers or terminals.
- The PXC Modular firmware, including the operating system, is stored in non-volatile flash memory.
- The PXC Modular provides both an Ethernet port as well as an RS-485 port for communication on Automation Level Networks using either TCP/IP or RS-485.
- An HMI RS-232 port is provided as a connection to a laptop computer for local operation and engineering.
- LEDs provide instant visual indication of overall operation, network communication, and low battery warning.
- Two self-forming buses are an integral part of the flexibility of the PXC Modular. A self-forming bus to the right of the controller supports up to 500 points through TX-I/O™ modules. Another self-forming bus to the left of the controller supports hardware connection to subsystems through Expansion Modules.

### TX-I/O Modules

TX-I/O Modules are modular expansion I/O consisting of an electronics module and terminal base. The electronics modules perform A/D or D/A conversion, signal processing, and point monitoring and command output through communication with the PXC Modular. The terminal bases provide for termination of field wiring and connection of a self-forming bus. For more information, see *TX-I/O* (149-476).

The TX-I/O Power Supply provides power for TX-I/O modules and peripheral devices. Multiple Power Modules can be used in parallel to meet the power needs of large concentrations of I/O points (Figure 2 and Figure 3). For more information, see *TX-I/O Power Supplies* (149-476).




Figure 2. TX-I/O Power Supply and TX-I/O Modules.



Figure 3. PXC Modular, TX-I/O Power Supply, and TX-I/O Modules.

### PXC Modular Expansion Module

The PXC Modular Expansion Module (see Figure 4) provides the hardware connection for Field Level Network (FLN) devices. Using the Triple RS-485 Expansion Module, the PXC Modular supports up to three RS-485 networks of Field Level Network devices (see Figure 5).



Figure 4. RS-485 Expansion Module.



Figure 5. RS-485 Expansion Module and PXC Modular.

## Modular Control Panels with Application Flexibility

The PXC Modular is a high performance controller with extensive flexibility to customize each field panel with the exact hardware and program for the application. As a result, the user only purchases what is needed.

For example, in monitoring applications, the control panel can be customized with the number and type of points to match the sensor devices. For monitoring and controlling a large number of (on-off) fans or